

Table des matières

Script d'optimisation automatique des bases 3

Script d'optimisation automatique des bases

Ce script optimise les bases de données MySQL présentes sous /var/lib/mysql.

```
#!/bin/bash

for base in `ls -l /var/lib/mysql/ | grep dr | grep -Ev "test|status|mail|dumps" | awk '{print $NF}'`
do
echo "use $base;" > /tmp/optmz_${base}.sql
echo -e "OPTIMIZE TABLE \c" >> /tmp/optmz_${base}.sql
for table in `ls -l /var/lib/mysql/$base/*.frm | awk -F "/" '{print $6}' | awk -F "." '{print $1}'`
do
echo -e "$table,\c" >> /tmp/optmz_${base}.sql
done
echo ";" >> /tmp/optmz_${base}.sql
cat /tmp/optmz_${base}.sql | sed "s/,;/;/g" > /tmp/optmz_${base}.sql.temp
mv /tmp/optmz_${base}.sql.temp /tmp/optmz_${base}.sql
done

for file in `ls -l /tmp/optmz*.sql`
do
mysql -u 'user' --password=XXXXXXXX < $file #'user' doit avoir les droits full
done

rm -f /tmp/optmz*.sql
```

From:
<https://unix.ndlp.info/> - Where there is a shell, there is a way

Permanent link:
https://unix.ndlp.info/doku.php/informatique:base_de_donnees:script_d_optimisation_automatique_des_bases

Last update: 2009/06/29 19:04