

Table des matières

Trouver les WWN 3

Trouver les WWN

```
Shell> drivers
      T D
D      Y C I
R      P F A
V  VERSION  E G G #D #C DRIVER NAME          IMAGE NAME
=====
16 00000020 B - - 6 17 PCI Bus Driver          PciBus
23 03050100 B X X 1 2 LSI Logic Fusion MPT SAS Driver  PciROM:02:01:00:001
27 00000220 D X X 1 - HP Fibre Channel Driver  PciROM:04:00:01:003
28 00000220 D X X 1 - HP Fibre Channel Driver  PciROM:04:00:00:003
34 00000020 D X - 1 - Usb Keyboard Driver      UsbKb

Shell> drvcfg 27
Configurable Components
  Drv[27] Ctrl[2B] Lang[eng]

Shell> drvcfg -s 27 2B
Set Configuration Options
  Drv[27] Ctrl[2B] Lang[eng]
Fibre Channel Driver Configuration Utility

NOTE: Do not redirect console output to a file.

Main Menu

NVRAM Parameters
 1. Edit Adapter Settings
 2. Edit Advanced Settings
 3. Edit Database
 4. Edit Boot Settings
Information
 5. Show Database
 6. Show Translation
 7. Show NVRAM Buffer
 8. Info
 9. Help
Operation
10. Abandon
11. Write
12. Quit

Enter a Selection: 8

Info

Adapter Path: Acpi(PNP0002,0300)/Pci(00|00)/Pci(00|01)
Adapter WWPN: 50014380072EA142
Adapter WWNN: 50014380072EA143
```

From:
<https://unix.ndlp.info/> - **Where there is a shell, there is a way**

Permanent link:
https://unix.ndlp.info/doku.php/informatique:nix:hp:hpx_efi

Last update: 2011/11/09 13:07