Table des matières

3

Trouver les WWN

| Shell> drivers T D | | |
|--|---|--|
| D YCI R PFA | | |
| V VERSION E G G #D #C DRIVER NAME | IMAGE NAME | |
| Image: second | = PciBUS PciROM:02:01:00:001 PciROM:04:00:01:003 PciROM:04:00:00:003 USbKb | |
| Shell> drvcfg 27 Configurable Components Drv[27] Ctrl[2B] Lang[eng] | | |
| Shell> drvcfg -s 27 28 Set Configuration Options Drv[27] Ctrl[2B] Lang[eng] Fibre Channel Driver Configuration Utility | | |
| NOTE: Do not redirect console output to a file. | | |
| Main Menu | | |
| NVRAM Parameters 1. Edit Adapter Settings 2. Edit Advanced Settings 3. Edit Database 4. Edit Boot Settings Information 5. Show Database 6. Show Translation 7. Show NVRAM Buffer 8. Info 9. Help 0peration 10. Abandon 11. Write 12. Quit | | |
| Enter a Selection: 8 | | |
| Info | | |
| Adapter Path: Acpi(PNP0002,0300)/Pci(00 00)/Pci(00 01) Adapter WWPN: 50014380072EA142 Adapter WWNN: 50014380072EA143 | | |
| | | |
| | | |
| From: https://unix.ndlp.info/ - Where there is a shell, there is a way | | |
| Permanent link: https://unix.ndlo.info/doku.php/informatique:nix:hp:hpux_efi | | |

Last update: 2011/11/09 13:07