Table des matières

Alternate rootvg 3
Installer un ifix - efix 3
Monter un cd 3
Monter une ISO 3
Rechercher un APAR 3
Activer les IO asynchrones sans rebooter 3
Mofidier la longueur max. des logins 3
Packages 4

Alternate rootvg

- Split du rootvg

```
bosboot -a
unmirrorvg rootvg hdisk1
reducevg rootvg hdisk1
alt_disk_copy -d hdisk1
bootlist -m normal hdisk0
```

- Suppression du alt_rootvg si tout est ok

```
alt_rootvg_op -X altinst_rootvg
extendvg -f rootvg hdisk1
mirrorvg rootvg hdisk1
bootlist -m normal -o hdisk0 hdisk1
```

- Activation du alt_rootvg comme master (si upgrade KO)

```
bootlist -m normal -o hdisk1
shutdown -Fr
alt_rootvg_op -X altinst_rootvg
extendvg –f rootvg hdisk1
mirrorvg rootvg hdisk1
bootlist -m normal -o hdisk0 hdisk1
bosboot -a
```

Installer un ifix - efix

```
emgr -e IY95543.070301.epkg.Z
```

Monter un cd

```
mount -Vr cdrfs /dev/cd0 /cdrom
```

Monter une ISO

- **AIX 5.1**

```
mklv -y cdlv -s n -L /dev/cdlv rootvg 700M hdisk0
dd if=/install/image.iso of=/dev/cdlv bs=32k
mount -v cdrfs -o ro /dev/cdlv /mnt
```

- **AIX 6.1**

```
loopmount -i /install/image.iso -o "-V cdrfs -o ro" -m /mnt
```

Rechercher un APAR

http://www-1.ibm.com/support/

Activer les IO asynchrones sans rebooter

```
chdev -l aio0 autoconfig=available
mkdev -l aio0
```

Mofidier la longueur max. des logins

AIX 5.3 only

```
lsattr -El sys0 -a max_logname
chdev -l sys0 -a max_logname=XX (XX--desired number)
lsattr -El sys0 -a max_logname
getconf LOGIN_NAME_MAX
shutdown -Fr
```

Packages

```
lslpp -L                        displays info about all installed filesets or fileset updates
lslpp -L <fileset>              displays info about that fileset
lslpp -h <fileset>              shows the history of the fileset
lslpp -l | grep <fileset>       shows if it is installed or not
lslpp -lc| grep <fileset>       shows the state (Aplp., Comm., Broken..) in /etc/objrepos and in /usr/lib/objrepos of a fileset

lslpp -f <fileset>              shows all files that are installed with  a particular fileset
lslpp -w /usr/local/bin/lsof    shows the fileset which contains the given file (binary) (which command shows full path: which lsof)

lslpp -p <fileset>              shows requisite information for a specified fileset (-p means possibly prerequisite)
lslpp -d <fileset>              shows filesets that are dependents on the specified fileset
```

From:
https://unix.ndlp.info/ - **Where there is a shell, there is a way**

Permanent link:
https://unix.ndlp.info/doku.php/informatique:nix:ibm:ibm_aix_tips

Last update: **2018/10/17 14:27**