Table des matières

/etc/samba/smb.conf

```
[global]
    workgroup = workgroup
    server string = Serveur toto
    log file = /var/log/samba/%m.log
    realm = serveur.ad.toto.fr
    security = ads
    template shell = /bin/bash
    idmap uid = 20000-50000000
    idmap gid = 20000-50000000
    winbind use default domain = yes
    winbind enum users = no
    winbind enum groups = no
    winbind separator = +
    allow trusted domains = no
    password server = X.X.X.X X.X.X.X
    wins server = X.X.X.X
    name resolve order = wins lmhosts host
    client use spnego = yes
    client ntlmv2 auth = yes
    encrypt passwords = yes
```

/etc/nsswitch.conf

```
passwd:     files nis winbind
shadow:     files nis winbind
group:      files nis winbind
```

/etc/krb5.conf

```
[logging]
 default = FILE:/var/log/krb5libs.log
 kdc = FILE:/var/log/krb5kdc.log
 admin_server = FILE:/var/log/kadmind.log

[libdefaults]
 default_realm = serveur.ad.toto.fr
 dns_lookup_realm = true
 dns_lookup_kdc = true

[realms]

 serveur.ad.toto.fr = {
  kdc = X.X.X.X
  kdc = X.X.X.X
  admin_server = X.X.X.X
  }

[kdc]
 profile = /var/kerberos/krb5kdc/kdc.conf

[appdefaults]
 pam = {
   debug = false
   ticket_lifetime = 36000
   renew_lifetime = 36000
   forwardable = true
   krb4_convert = false
 }
```

Joindre le domaine :

```
net ads join -UAdministrator
```

Tester :

```
wbinfo -u ID
```